

chybí
obrázek

Doporučená cena
0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 15,60
rám Sumnum 27,5 Stealth Full Carbon, Zero Suspension System, 205mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, 12x150mm rear axle, 83mm BSA bottom bracket, MAX. capacity sealed bearings, internal cable routing, ISCG 05. *Geometry Kit included.	vidlice Fox 40 27,5 Float FIT HSC LSC EVOL Factory Kashima 203mm, Air Spring, 1-1/8” steerer tube, 20mm axle. Settings: high and low-speed compression, rebound, air preload.
hlavové složení Internal Onoff Mercurium 1.5 ZS for 1-1/8” head tube. 41x30.15x7x45? ACB sealed bearings, with cups from the geometry kit. External diameter 56mm.	přehazovačka Shimano Saint RD-M820-SS 10s. Shadow Plus technology. Short cage.
přesmykač E.13 LG1R Carbon chain guide, IFD DMB (Direct Mount Bashguard) Gen 2 Stealth Idler, Aluminum hardware, adjustable/replaceable lower armature, solvent-resistant polycarbonate, larger ISCG 05 mount holes, adjustable upper slider opens without tools.	řazení Shimano Saint SL-M820 10s. Low friction dual sealed bearings. Multi Release.
brzdové páčky Shimano Saint, ICE technology, ergonomic antiskid lever with servo wave, free stroke and tool less reach adjust.	kliky Shimano Saint M825. HOLLOWTECH II technology,165mm.
středové složení Shimano 83mm.	řídítka Renthal Fatbar series 7 alloy, rise: 30mm, width: 780mm, 7? backsweep, 5? upsweep, 31.8mm barbore.
představec Onoff Stoic DH Integrated FG, 20-30mm adjustable length. 6061 aluminium, 31.8mm barbore.	pedály /
sedlovka SDG I-Beam SP-951 Carbon 31.6 300mm length, micro-adjustment.	sedlo SDG I-beam I - Fly 2.0 Eva. High-grade microfibre, sides with Kevlar protection.
náboj přední DT Classic 240 20x110mm, IS 6 bolts	náboj zadní DT Classic 240 Ratchet system 12X150mm, IS 6 bolts
řetěz Shimano HG95 10s.	kazeta Shimano Ultegra CS-HG6700, 11-25T, 10s.
dráty DT competition, black	ráfky Dt Swiss FR1950 27’5, 33mm external width, tubeless ready. 32 holes
pláště Maxxis Minion DHR II 27’5 x 2.4 Super Tacky Compound, Wire	tlumič Fox DHX2 Factory Kashima 222x70mm. Settings: High and low-speed compression, high and low-speed rebound, spring preload. Super Light Steel (SLS) Spring.