

chybí obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 12,40
rám Vantage 27,5 6061 Alloy Stealth Evo, hydroformed tubing, Forward Geometry, Tapered head tube, BSA bottom bracket, telescopic seatpost internal routing, 12x148mm rear axle.	vidlice Fox 34 27,5 Rhythm Sweep adjust EVOL, 140mm, lever with 2 positions plus intermediate positions in low/high-speed compression, Tapered head tube, 15x110mm axle. Settings: rebound, compression adjustment at high/low-speed to lock, air preload.
hlavové složení Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.	přehazovačka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system
přesmykač /	řazení Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation
brzdové páčky Sram Guide R, tools-free Reach adjust, ambidextrous lever mount.	kliky Sram NX1, forged 6066 aluminium, 24mm axle, chainring Direct mount, 170mm crank arm length in S/M size and 175mm in L/XL size
středové složení Sram GXP XR, sealed bearings, 73mm	řídítka Mondraker aluminium 6061 double butted. Exclusive Vantage RR design, 0.5" rise, 760mm width, 9° backsweep, 5° upsweep, 31.8mm barbore
představec Onoff Stoic FG 30mm. 6061 forged aluminium. 31.8mm barbore	pedály /
sedlovka Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.	sedlo Mondraker Vantage RR exclusive design.
náboj přední Mavic Boost axle 15x110mm, sealed bearings, IS 6 bolts mount.	náboj zadní Mavic, Boost axle 12x148mm, sealed bearings, TS-2 freehub, IS 6 bolts mount.
řetěz Sram PC-1110 11s	kazeta Sunrace CSMS8, 11-46T, 11s.
dráty Mavic Steel, straight-pull.	ráfky Mavic XA 27,5, Tubeless Ready, internal width 25mm, asymmetrical rim, hookless, 24 spokes.
pláště Maxxis High Roller II 27,5x2.3 Tubeless Ready, Dual compound, Exo Protection, 60TPI, foldable.	tlumič /
přední brzda Sram Guide R 180mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads	zadní brzda Sram Guide R 180mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads
omotávka Maxxis Ardent 27,5x2.4 Tubeless Ready, Dual compound, Exo Protection, 60TPI, foldable.	převodník 32T, X-SYNC 1x11 technology

