

Doporučená cena
0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	**rám** e-Crafty 27,5 6061 Alloy Stealth Evo, Bosch Performance CX system with integrated removable battery, Zero Suspension System, Forward Geometry, Boost 12x148mm rear axle, Tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, exclusive plastic motor covers, shock mudguard integrated in the swingarm, travel 140mm.
vidlice Fox 36 27´5 Float Grip Evol Performance, 160mm, 3 positions lever with intermediate positions in low/high-speed compression, Tapered steerer tube, 15x110mm Boost axle. Settings: rebound, Compression Open to Firm, air preload.	**hlavové složení** Onoff Saturn Tapered for 1-1/8” -> 1/5” head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.
přehazovačka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system.	**přesmykač** /
řazení Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation.	**brzdové páčky** Sram Guide RE, tools-free Reach adjust, ambidextrous lever mount.
středové složení /	**řidítka** Mondraker custom design 1.0 780mm.
představec Onoff Stoic FG 30mm. Forged 6061 alloy, 31.8mm barbore.	**sedlovka** Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.
sedlo Mondraker E-mtb exclusive design.	**náboj přední** DT Swiss H1900 Boost 15x110mm.
náboj zadní DT Swiss H1900 Boost 12x148mm.	**řetěz** Sram PC 1110 11s.
kazeta Sram PG-1130 11-42T 11s.	**dráty** CN stainless.
ráfky DT Swiss H1900 27,5 35mm Boost.	**plášť** Maxxis Minion DHF 27,5x2.8, tubeless ready, Dual compound, Exo Protection, 60TPI, folding.
tlumič Fox Float DPX2 LV EVOL Performance. Settings: rebound, compression (3 positions), air preload. 205x62.5mm. Trunnion top mount, 22.2x10mm bottom bushes.	**přední brzda** Sram Guide RE 200mm, 4-piston caliper derived from the Code brake, centerline 6 bolts one-piece rotor, semi-metallic pads
zadní brzda Sram Guide RE 200mm, 4-piston caliper derived from the Code brake, centerline 6 bolts one-piece rotor, semi-metallic pads	**omotávka** High Roller 27 II,5x2.8, tubeless ready, Dual compound, Exo Protection, 60TPI, folding.
nastavení tlumiče Light compresion, light rebound, 0.6 internal reducer.	