

Doporučená cena
0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	**hmotnost** 13,80
rám Dune 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, Forward Geometry, Boost 12x148mm rear axle, Tapered head tube, One piece Monoblock upper link, BSA bottom bracket, telescopic seatpost internal routing, Max. capacity sealed bearings, shock mudguard, ISCG 05, removable derailleur adaptor, sideswing front derailleur, 160mm travel.	**vidlice** Fox 36 27,5 Float Grip EVOL Performance 170mm, lever with 3 positions plus intermediate positions in low/high-speed compression. Tapered head tube, 15x110mm axle. Settings: rebound, high/low-speed compression to lock, air preload.
hlavové složení Onoff Saturn Tapered for 1-1/8” -> 1/5” head tube. ACB sealed bearings, top 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.	**přehazovačka** Sram GX Eagle Type 3 with Roller Bearing Clutch and Cage Lock, 1x12s, long cage, X-Horizon system.
přesmykač /	**řazení** Sram Trigger GX Eagle 12s, X-Actuation, Zero Loss Technology.
brzdové páčky Sram Guide R, tools-free Reach adjust, ambidextrous lever mount.	**kliky** Truvativ Descendant 7K Eagle, aluminium crank arms, 24mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S/M size and 175mm in L/XL size.
středové složení SRAM GXP XR, sealed bearings, 73mm.	**řidítka** Mondraker aluminium 6061 double butted. Exclusive Dune R design, 1” rise, 780mm width, 9? backsweep, 5? upsweep, 31.8mm barbore
představec Onoff Stoic FG 30mm. 6061 forged aluminium. 31.8mm barbore	**pedály** /
sedlovka Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.	**sedlo** SDG Circuit MTN, High-density PU, black steel rail, Cordura sides
náboj přední Mavic Boost axle 15x110mm, sealed bearings, IS 6 bolts mount.	**náboj zadní** Mavic, Boost axle 12x148mm, sealed bearings, TS-2 freehub for XD, IS 6 bolts mount.
řetěz SRAM GX Eagle 12s.	**kazeta** SRAM XG-1275 10-50T, XD freehub for 12s.
dráty Mavic Steel, straight-pull.	**ráfky** Mavic XA 27,5, Tubeless Ready, internal width 25mm, asymmetrical rim, hookless, 24 spokes.
pláště Maxxis High Roller II 27’5 x 2.3 Tubeless Ready, Dual compound, Exo protection, 60TPI, folding	**tlumič** Fox Float DPX2 LV EVOL Performance. Settings: rebound, compression (3 positions), air preload. 215x63.5mm. Trunnion top mount, 22.2x10mm bottom bushes.
přední brzda Sram Guide R 200mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads	**zadní brzda** Sram Guide R 180mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads
omotávka Maxxis High Roller II 27’5 x 2.3 Tubeless Ready, Dual compound, Exo protection, 60TPI, folding	**nastavení tlumiče** Medium compression, light rebound, 0.6 internal reducer.

převodník
34T, molded aluminium series 7000, narrow wide 1x11 technology.

patka k přehazovačce
Mondraker M066