

chybí
obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 16,50
rám Summum 27,5 Stealth Full Carbon, Zero Suspension System, 205mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, 12x150mm rear axle, 83mm BSA bottom bracket, MAX. capacity sealed bearings, internal cable routing, ISCG 05. *Optional Geometry Kit.	vidlice Fox 40 27,5 Float FIT4 LSC EVOL Performance Elite 203m, Air Spring, 1-1/8” steerer tube, 20mm axle. Settings: low-speed compression, rebound, air preload.
hlavové složení Onoff Mercurium 1.5 ZS for 1-1/8” head tube. 41x30.15x7x45?x45? ACB sealed bearings, External diameter 56mm.	přehazovačka Shimano Zee RD-M640-SS 10s. Shadow Plus technology. Short cage.
přesmykač E.13 LG1 chain guide DMB (Direct Mount Bashguard) Gen 2 Stealth Idler, Aluminum hardware, adjustable/replaceable lower armature, solvent-resistant polycarbonate, larger ISCG 05 mount holes, adjustable upper slider opens without tools	řazení Shimano Zee SL-M640 10s. 2-way Release.
brzdové páčky Sram Guide R, tools-free Reach adjust, ambidextrous lever mount.	kliky Shimano Zee M645, alloy, reinforced steel axle. 165mm.
středové složení Shimano 83mm.	řídítka Mondraker double butted 6061 aluminium, exclusive design for Summum Pro, 1” rise, 780mm width, 9? backsweep, 5? upsweep, 31.8mm barbore
představec Onoff Stoic DH Integrated FG, 20-30mm adjustable length. 6061 aluminium, 31.8mm barbore	pedály /
sedlovka SDG I-Beam SP-751 Alloy 31.6, 300mm length and micro-adjustment	sedlo SDG I-Beam I-Fly 2.0. High-density PU, lateral protection in cordura.
náboj přední MDK Disc Pro DH 20x110mm, IS 6 bolts	náboj zadní MDK Disc Pro DH 12x150mm, sealed bearings, IS 6 bolts
řetěz Shimano HG95 10s.	kazeta Shimano CS-HG500-10 11-25T, 10s.
dráty CN stainless steel butted 2.0-1.8-2.0	ráfky Dt Swiss FR570 27’5, 33mm external width, tubeless ready. 32 holes
pláště Maxxis Minion DHR II 27’5 x 2.4 Super Tacky Compound, Wire	tlumič Fox DHX2 Performance Elite 222x70mm, Settings: low-speed compression, rebound, spring preload.
přední brzda Sram Guide R 203mm, lightweight 4-piston dual-diameter caliper, G2 6 bolts one-piece rotor, semi-metallic pads	zadní brzda Sram Guide R 203mm, lightweight 4-piston dual-diameter caliper, G2 6 bolts one-piece rotor, semi-metallic pads

omotávka

Maxxis Minion DHR II 27'5 x 2.4 Super Tacky Compound, Wire

převodník

aluminium, 36T.

ostatní

*Optional Geometry Kit: Chainstay adaptors for 445mm, 450mm, 455mm, 460mm. Headset cups: 0?, /- 1?, /-2?. Brake adaptors: 455mm, 460mm

nastavení tlumiče

Firm compression , light rebound, S size spring 450 lbs, M size spring 500 lbs, L/XL 550 lbs spring

patka k přehazovačce

Mondraker M063.