

chybí obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti M , L , XL	hmotnost 10,70
rám Chrono 29er Stealth 2.0 Carbon, PF30 bottom bracket, Tapered head tube, HHG Internal Cable Routing, 12x142mm rear axle, Comfort Flat chainstays (Flatstays) design.	vidlice RockShox SID 29 RL Solo Air 100mm, tapered steering tube, 15x100mm axle, 30mm aluminium stanchions. Settings: Rebound, low-speed compression until lock-out, air preload
hlavové složení Onoff Titan internally Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41.8x30.5x8x45?x45?, bottom 51.9x40x8x45?x45?.	přehazovačka Sram GX Eagle Type 3 with Roller Bearing Clutch and Cage Lock, 1x12s, long cage, X-Horizon system.
přesmykač /	řazení Sram Trigger GX Eagle 12s, X-Actuation, Zero Loss Technology.
brzdové páčky SRAM Level T, brake lever reach adjust, 2 bolts clamp Matchmaker compatible, ambidextrous lever mount.	kliky Truvativ Stylo 6k Eagle, 6000 series aluminium crank arms, 24mm axle, chain ring with Direct Mount, 170mm crank arm length in S/M size and 175mm in L/XL size.
středové složení SRAM PF30sealed bearings.	řídítka Onoff Notion 0.2. Aluminium 6061 T6 double butted. 4.8mm rise, 710mm width, 9? backsweep, 0? upsweep, 31.8mm barbare
představec Onoff Notion. 3D forged 6061 T6 aluminium, /-6? angle, 31.8mm barbare. Size M 80mm length, size L/XL 90mm length	pedály /
sedlovka Onoff Notion 0-R. Forged head 2014 T6 aluminium. 31.6mm diameter, 400mm length	sedlo Exclusive Mondraker XC Chrono 29er design
náboj přední Mavic, Boost 15x110mm axel, sealed bearings, IS 6 bolts mount.	náboj zadní Mavic, Boost 12x142mm axel, sealed bearings, TS-2 XD freehub, IS 6 bolts mount.
řetěz SRAM GX Eagle 12s.	kazeta SRAM XG-1275 10-50T, XD freehub for 12s.
dráty Mavic steel, straight pull,.	ráfky Mavic Crossmax 29, Tubeless Ready, 22mm internal width, asymetric, hookless, 24 spokes
pláště Maxxis Ikon Exo 29x2.35, 60 TPI, folding.	tlumič /
přední brzda Sram Level T 160mm, centerline 6 bolts one-piece rotor, organic pads	zadní brzda Sram Level T 160mm, centerline 6 bolts one-piece rotor, organic pads
omotávka Maxxis Ikon Exo 29x2.35, 60 TPI, folding.	převodník 32T Direct Mount, aluminium, X-SYNC 2.
patka k přehazovačce Mondraker M066.	ostatní 12x142mm rear axle with QR.