

chybí obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 13,60
rám Foxy 27,5 Stealth Air full Carbon Structure, Zero Suspension System, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, BSA 73mm bottom bracket, dedicated 1x drivetrain design, Tapered head tube, HHG internal cable routing, Enduro MAX sealed bearings, mudguard for shock, ISCG 05, custom chainstay protector, carbon fabric protector in the diagonal tube, 150mm of travel. *Optional Geometry Kit.	vidlice RockShox Pike 27,5 RCT3, Charger 2, Debon Air, 160mm, Tapered head tube, 15x110mm axle. Settings: rebound, compression adjustment with 3 positions (open/pedal/firm) plus adjustment at low-speed, air preload.
hlavové složení Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. ACB sealed bearings, top 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.	přehazovačka Sram GX Eagle Type 3 with Roller Bearing Clutch and Cage Lock, 1x12s, long cage, X-Horizon system.
přesmykač /	řazení Sram Trigger GX Eagle 12s, X-Actuation, Zero Loss Technology.
brzdové páčky Shimano XT M8000, Servo Wave stem adjustment, lever reach adjustment.	kliky Truvativ Descendant Eagle Carbon, carbon crank arms, 24mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S/M size and 175mm in L/XL size.
středové složení SRAM GXP XR, sealed bearings, 73mm.	řídítka Onoff Stoic Carbon. Exclusive Foxy Carbon XR design, 0.5" rise, 780mm width, 9? backsweep, 5? upsweep, 35mm barbare
představec Onoff Stoic FG 30mm. 6061 forged aluminium. 35mm barbare	pedály /
sedlovka Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.	sedlo SDG Fly MTN, High-density PU, steel rails, cordura sides.
náboj přední DT Spline 15x110mm, IS 6 bolts mount.	náboj zadní DT Spline 12X148mm, XD freehub, IS 6 bolts mount.
řetěz SRAM GX Eagle 12s.	kazeta SRAM XG-1275 10-50T, XD freehub for 12s.
dráty DT Competition, straight.	ráfky DT Swiss M1700 Spline 27,5, internal width 30mm.
pláště Maxxis High Roller II 27'5 x 2.3 tubeless ready, dual compound, Exo protection, 60TPI, folding	tlumič RockShox Superdeluxe Coil RCT. Settings: rebound, compression (2 positions: Open/Pedal), compression adjustment at low-speed with 3 positions in Open mode, preload. 205x62.5mm. Trunnion top mount, 22.2x10mm bottom bushes.
přední brzda Shimano XT M8000, Ice-Tech resin pads, RT76 203mm disc with 6 screws.	zadní brzda Shimano XT M8000, Ice-Tech resin pads, RT76 180mm disc with 6 screws.
omotávka Maxxis High Roller II 27'5 x 2.3 tubeless ready, dual compound, Exo protection, 60TPI, folding	nastavení tlumiče Firm compression, light rebound, size S - 400lbs spring, M - 450lbs spring, L/XL - 500lbs spring.

převodník

34T Direct Mount, CNC-machined aluminium, X-SYNC 2.

patka k přehazovačce

Mondraker M071.

ostatní

* Optional Geometry Kit: chainstay adapters to 435mm. Headset cups +/- 1?.
