

PRIME, BLACK/WHITE, 2021

obj. č. 010.21206



Technické specifikace

barva rámečku
black/white

vyráběné velikosti
XS 380mm / S 390mm / M 430mm / L 470mm / XL 510mm

hmotnost
21,9 Kg

rám
Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

vidlice
RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset.
Settings: compression adjustment at low-speed to lock, rebound, air preload

hlavové složení
Onoff Saturn tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41x30.2x7x45x45, bottom 51.9x40x8x45x45

přehazovačka
Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

řazení
Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky
Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

kliky
Race Face Aeffect ebike, 165mm

řídítka
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm

představec
Onoff Sulfur FG 30mm 0, 6061 forged alloy, 31.8mm barbore

sedlovka
Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm

sedlo
Mondraker e-MTB custom design

náboj přední
Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

náboj zadní
Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

řetěz
Sram SX Eagle, 12s, Powerlock

kazeta
Sram PG-1210, 11-50T, 12s

dráty
CN round stainless steel

ráfky
MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

pláště
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

obj.c.
010.21206

přední brzda
Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad

zadní brzda
Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad


omotávka
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

patka k přehazovačce
Mondraker M068

převodník
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

motor+baterie
Bosch Performance Line CX Cruise (25Km/h) GEN4, computer Bosch Purion, Bosch Powertube 625Wh

Geometrie



GEOMETRY

Size	XS	S	M	L	XL
A Seat Tube Length	380 mm	390 mm	430 mm	470 mm	510 mm
B Top Tube Length	600 mm	615 mm	645 mm	670 mm	700 mm
C Bottom Bracket Drop	-60 mm	-60 mm	-60 mm	-60 mm	-60 mm
D Bottom Bracket Height	318 mm	318 mm	318 mm	318 mm	318 mm
E Chainstay Legth	455 mm	455 mm	455 mm	455 mm	455 mm
F Seat Tube Angle, Actual	73.5°	73.5°	73.5°	73.5°	73.5°
G Seat Tube Angle, Effective	73.5°	73.5°	73.5°	73.5°	73.5°
H Head Tube Angle	69°	69°	69°	69°	69°
I Fork Offset	51 mm	51 mm	51 mm	51 mm	51 mm
J Wheelbase	1138mm	1153 mm	1183 mm	1210 mm	1240 mm
K Head Tube Length	110 mm	110 mm	110 mm	130 mm	130 mm
L Reach	410 mm	425 mm	455 mm	480 mm	505 mm
M Stack	640 mm	640 mm	640 mm	658 mm	658 mm