

chybí
obrázek

Doporučená cena

0 Kč

Technické specifikace

barva rámečku vibrant blue/yellow	vyráběné velikosti S , M , L , XL
hmotnost 13,60	rám Foxy 27,5 Stealth Air full Carbon Structure, Zero Suspension System, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, BSA 73mm bottom bracket, dedicated 1x drivetrain design, Tapered head tube, HHG internal cable routing, Enduro MAX sealed bearings, mudguard for shock, ISCG 05, custom chainstay protector, carbon fabric protector in the diagonal tube, 150mm of travel. *Optional Geometry Kit.
vidlice Rockshox Revelation RC Solo Air, 150mm, Tapered head tube, 15x110mm axle. Settings: rebound, compression adjustment at low-speed to lock, air preload.	hlavové složení Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.
přehazovačka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system.	řazení Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation.
brzdové páčky Shimano MT-500, small lever for braking with 2 fingers.	kliky SRAM NX16000 series aluminium, 24mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S/M size and 175mm in L/XL size.
středové složení SRAM GXP XR, sealed bearings, 73mm.	řídítka Mondraker aluminium 6061 double-Tapered. Exclusive design for Foxy Carbon R, height 20mm, width 780mm, 9° backsweep, 5° upsweep, diameter 31.8mm.
představec Onoff Stoic FG 30mm. Molded aluminium 6061, handlebar diameter 31.8mm.	pedály /
sedlovka Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.	sedlo Mondraker Foxy Carbon R exclusive design.
náboj přední MDK DC511 15x110mm, sealed bearings, IS 6 bolts mount.	náboj zadní MDK GW 12x148mm, sealed bearings, IS 6 bolts mount.
řetěz SRAM PC-1110 11s.	kazeta Sunrace CSMS8, 11-46T, 11s.
dráty CN round stainless steel.	ráfky MDK-EP1 27,5 TLR ASY, internal width 27mm, tubeless ready, 32 spokes.
pláště Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.	obj.c. 010.18071
tlumič RockShox Deluxe RL Debonair. Settings: rebound, compression (2 positions: Open/Pedal), air preload. 205x62.5mm. Trunnion top mount, 22.2x10mm bottom bushes.	přední brzda Shimano MT-500, Servo Wave technology, aluminium clamp, mineral oilresin pads, 180mm single-piece disc with 6 holes.

zadní brzda

Shimano MT-500, Servo Wave technology, aluminium clamp, mineral oilresin pads, 180mm single-piece disc with 6 holes.

nastavení tlumiče

Medium compression, medium rebound, lock out firm 430, 2 internal reducers.

patka k přehazovačce

Mondraker M071.

omotávka

Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.

převodník

32T, steel, X-SYNC 1x11 technology.

ostatní

* Optional Geometry Kit: chainstay adapters to 435mm. Headset cups +/- 1?.