

chybí obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 13,80
rám Foxy 27,5 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, Forward Geometry, Boost 12x148mm rear axle, One piece Monoblock upper link, BSA bottom bracket, telescopic seatpost internal routing, MAX capacity sealed bearings, removable derailleur adaptor, sideswing derailleur, 140mm travel.	vidlice Rockshox Reba 27,5 RL Solo Air, 150mm, Tapered head tube, 15x110mm Boost axle, 32mm aluminium bars. Settings: rebound, compression adjustment at low-speed to lock, air preload.
hlavové složení Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.	přehazovačka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system.
řazení Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation.	brzdové páčky SRAM Level T, brake lever reach adjust, 2 bolts clamp Matchmaker compatible, ambidextrous lever mount.
kliky SRAM NX16000 series aluminium, 24mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S/M size and 175mm in L/XL size.	středové složení SRAM GXP XR, sealed bearings, 73mm.
řídítka Mondraker 6061 Aluminium 6061 double-Tapered. Exclusive design for Foxy, height 20mm, width 780mm, 9? backsweep, 5? upsweep, diameter 31.8mm.	představec Onoff Stoic FG 30mm. 6061 forged aluminium. 31.8mm barbore
pedály /	sedlovka Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.
sedlo Exclusive Mondraker Foxy R design	náboj přední MDK DC511 15x110mm, sealed bearings, IS 6 bolts mount.
náboj zadní MDK GW 12x148mm, sealed bearings, IS 6 bolts mount.	řetěz SRAM PC-1110 11s.
kazeta Sunrace CSMS8, 11-46T, 11s.	dráty CN round stainless steel.
ráfky MDK-EP1 27,5 TLR ASY, internal width 27mm, tubeless ready, 32 spokes.	pláště Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.
tlumič RockShox Monarch RT Solo Air HV tube. Settings: rebound, compression (3 positions), air preload. 200x57mm. Bushes 22.2x10mm on both sides.	přední brzda Sram Level T 180mm, centerline 6 bolts one-piece rotor, organic pads
zadní brzda Sram Level T 180mm, centerline 6 bolts one-piece rotor, organic pads	omotávka Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.
nastavení tlumiče Light compresion L, L3 rebound , 380 Lbs Threshold. Eyelet High Volume.	převodník 32T, steel, X-SYNC 1x11 technology.
patka k přehazovačce Mondraker M066.	