

Doporučená cena
0 Kč

Technické specifikace

barva rámečku black/light blue/yellow	**vyráběné velikosti** S , M , L , XL
hmotnost 14,40	**rám** Dune 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, Forward Geometry, Boost 12x148mm rear axle, Tapered head tube, One piece Monoblock upper link, BSA bottom bracket, telescopic seatpost internal routing, Max. capacity sealed bearings, shock mudguard, ISCG 05, removable derailleur adaptor, sideswing front derailleur, 160mm travel.
vidlice RockShox Yari 27.5” RC 170mm, Tapered head tube, 15x110mm axle. Settings: rebound, compression adjustment at low-speed to lock, air preload.	**hlavové složení** Onoff Saturn Tapered for 1-1/8” -> 1/5” head tube. ACB sealed bearings, top 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.
přehazovačka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system	**přesmykač** /
řazení Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation	**brzdové páčky** Sram Level T, brake lever length adjust, interchangeable brake lever, clamp with two bolts compatible with Matchmaker
kliky FSA Gamma 2x10, aluminium cranks, 170mm crank arm length in S/M size and 175mm in L/XL size	**středové složení** Sram GXP XR, sealed bearings, 73mm
řidítka Mondraker aluminium 6061 double butted. Exclusive Dune design, 1” rise, 780mm width, 9? backsweep, 5? upsweep, 31.8mm barbore	**představec** Onoff Stoic FG 30mm. 6061 forged aluminium. 31.8mm barbore
pedály /	**sedlovka** Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.
sedlo SDG Fly MTN, High-density PU, steel rail, black Cordura sides	**náboj přední** MDK DC511 15x110mm, sealed bearings, IS 6 bolts mount.
náboj zadní MDK GW 12x148mm, sealed bearings, IS 6 bolts mount.	**řetěz** SRAM PC-1110 11s.
kazeta Sunrace CSMS7, 11-42T, 11s.	**dráty** CN round stainless steel.
ráfky MDK-EP1 27,5 TLR ASY, asymmetrical rim, internal width 27mm, tubeless ready, 32 spokes.	**plášť** Maxxis High Roller II 27,5x2.3 Tubeless Ready, Dual compound, Exo Protection, 60TPI, folding
obj.c. 010.18087	**tlumič** RockShox Monarch Plus R, Settings: Rebound, air preload, 215x63.5mm, 22.2x10mm bushings on both sides
přední brzda Sram Level T, 180mm, organic pads, 6-bolts one-piece rotor	**zadní brzda** Sram Level T, 180mm, organic pads, 6-bolts one-piece rotor

omotávka Maxxis Ardent 27’5 x 2.40, Single compound, 60 TPI, Wire	**nastavení tlumiče** Medium compression, light rebound 3, Standard Body
převodník 32T, steel, X-SYNC 1x11 technology	**patka k přehazovačce** Mondraker M066.