

chybí obrázek

Doporučená cena

0 Kč

Technické specifikace

vyráběné velikosti S , M , L , XL	hmotnost 9,20
rám Podium 29er Stealth Air Carbon, redesigned internal structure , Integrated Stem Technology (IST EVO), XC Forward Geometry, PF30 bottom bracket, Tapered head tube, HHG internal cable routing, Boost rear axel 12x148mm, Flatmount brake compatible, steel chain protector.	vidlice Fox 32 Step Cast Float 29 Performance, GRIP, EVOL, Tapered head tube, remote locking control, 15x110mm Boost axle, travel 100mm. Settings: rebound, lock, air preload.
hlavové složení Onoff Titan internally Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41.8x30.5x8x45?x45?, bottom 51.9x40x8x45?x45?.	přehazovačka SRAM X01 Eagle Type 3 with Roller Bearing Clutch and Cage Lock, 1x12s, long cage, X-Horizon system.
přesmykač /	řazení Sram Trigger GX Eagle 12s, X-Actuation, Zero Loss Technology.
brzdové páčky Sram Level TLM, brake lever reach adjust, pivot bearings, ambidextrous lever mount.	kliky Rotor REX 2.1, CNC machined aluminium 7055, 30mm axle, 170mm crank arm length in S size and 175mm in M/L/XL size.
středové složení Rotor 4630, PF30, sealed bearings.	řídítka Onoff Peak Carbon 0.2. 4.8mm rise, 710mm width, 9? backsweep, 0? upsweep, 31.8mm barbore
představec Stealth Carbon Integrated, sizes S/M: 85mm, sizes L/XL: 100mm length	pedály /
sedlovka Onoff Peak Carbon 0-R. 27.2mm. Diameter. 400mm length	sedlo Fizik Antares R7.
náboj přední Mavic, Boost 15x110mm axel, sealed bearings, IS 6 bolts mount.	náboj zadní Mavic, Boost 12x148mm axel, sealed bearings, TS-2 XD freehub, IS 6 bolts mount.
řetěz SRAM GX Eagle 12s.	kazeta SRAM XG-1275 10-50T, XD freehub for 12s.
dráty Mavic steel, straight pull, profiled, double butted.	ráfky Mavic Crossmax Light 29, Tubeless Ready, 22mm internal width, asymetric, hookless, 24 spokes
pláště Maxxis Ikon 3CMaxx Speed TR 29x2.20, tubeless ready, double compound, 120TPI, folding	tlumič /
přední brzda Sram Level TLM, monoblock caliper, organic pads, 160mm 6 bolts one-piece rotor	zadní brzda Sram Level TLM, monoblock caliper, organic pads, 160mm 6 bolts one-piece rotor
omotávka Maxxis Ikon 3CMaxx Speed TR 29x2.20, tubeless ready, double compound, 120TPI, folding	převodník NOQ 34T, CNC-machined aluminium 7055, narrow-wide.
patka k přehazovačce Mondraker M068.	ostatní Boost 12x148mm rear axle.